

Operating Manual



HYPERION⁺
A Meech Innovation

Hyperion 906
Power Unit

Contents

1.	Safety instructions.....	1
1.1.	Definition of safety warnings & symbols.....	1
1.2.	General safety	2
1.3.	Electrical safety	2
2.	Introduction	3
3.	Package contents	4
3.1.	Options.....	4
4.	Component overview.....	5
4.1.	906 HL variants	6
5.	Installation	7
5.1.	Mechanical installation	7
5.2.	Ionising product connection	8
6.	Grounding & 24VDC supply.....	14
6.1.	Meech 24VDC switchmode power supply	14
6.2.	Customers own 24VDC power supply	14
7.	Operation	15
7.1.	Using a BarMaster.....	15
7.2.	Using a SmartControl Touch.....	16
7.3.	Modifying the output parameters	17
7.3.1.	Health monitoring.....	17
7.3.2.	Voltage	18
7.4.	Remote control	18
7.4.1.	24VDC input port	18
7.4.2.	Software.....	19
8.	Monitoring	20
8.1.	Status LED	20
8.1.1.	Real Time Fault Monitoring codes	21
8.2.	Remote monitoring.....	22
8.2.1.	Alarm outputs.....	22
8.2.2.	Alarm output drive options.....	22
9.	Technical & construction data.....	24
10.	Technical drawings	25
11.	Maintenance	28
12.	CE approval	28
13.	UL approval	28
14.	Health & safety	28
15.	Repairs & warranty.....	28





Products shown in this document may be covered by one or more patents, patents applied for and/or registered designs and/or trademarks. For further information, please refer to our head office or visit www.meech.com.

1. Safety instructions

Before using this product, read the following safety and operating notes to ensure your own personal safety and to help protect your equipment. Failure to do so could result in injury. Connected equipment may require additional safety instructions. Observe all safety instructions for additional equipment before operating.

1.1. Definition of safety warnings & symbols

Safety and operating notes found in the document will be supplemented with the following warnings and symbols.

Safety warnings	Caution	A low-risk hazardous situation where minor or moderate injury can occur.
	Notice	A low-risk hazardous situation where damage to the equipment & products can occur.
Symbols	General hazard 	This symbol draws attention to a hazardous situation.
	Electrical shock 	This symbol draws attention to the risk of electrical shock.
	Notice 	This symbol draws attention where instructions must be followed.
	Referral 	This symbol instructs the reader to consult to a separate information source.

1.2. General safety

Before setting up the equipment:

- Read the operating instructions carefully and ensure you understand how to correctly use the equipment.
- Installation & testing must only be completed by suitably qualified personnel.
- Inspect the working environment and ensure it is clean and clear of hazards before removing equipment from packaging & product installation.
- Visually check all equipment for damage. If damaged, contact your local Meech representative before continuing.
- Always keep a copy of the operating manual close to the system to refer to.

1.3. Electrical safety


Before working on the equipment:

- Before installing or performing maintenance on the equipment, ensure the system is electrically isolated. Failure to do so could result in injury.
- Check the equipment and cables for any damage. If damaged, contact your local Meech representative before continuing.
- Ensure all wiring is completed by suitably qualified personnel.
- Check all wiring connections are correct in relation to the wiring diagrams later in this manual.

2. Introduction

The Hyperion 906 Power Unit is powered from a 24VDC power supply and produces an adjustable output of 2 to 7kVAC, 5mA max, suitable for any Meech AC ionising product.

Settings & configurations can be set using either a Meech BarMaster or SmartControl Touch.



Hyperion 906

3. Package contents

Carefully examine the packaging and its contents before use. If damage is evident, do not destroy the packaging and immediately notify the carrier of a possible damage claim. Shipping claims must be made by the consignee to the carrier.

The following items will be found inside the 906 packaging:

Item	Product code	
Hyperion 906 Power Unit	906 variant	Variant model code
	906	A906-5kV
		A906-7kV
	906 HL 5kV [†]	A906HL-5kV
	906 HL 7kV [‡]	A906HL-7kV
Earth cable	D3310	
Quick start guide	M0053	

* = Only one 906 unit is included

† = Suitable for 914EX

‡ = Suitable for 915EX



Caution – Risk of injury & equipment damage.

Observe correct manual handling procedures when removing the 906 from its packaging


3.1. Options

The following items can be purchased from Meech to supplement & provide extra functionality to the 906.

Item	Product code	
Switchmode power adaptor 48W <i>Switchmode Power Adaptors take the local electrical supply and convert it to a stable and filtered 24VDC output.</i>	A900IPS-SM-48W-STRIP A900IPS-SM-48W-EURO A900IPS-SM-48W-UK A900IPS-SM-48W-USA	Stripped Ends Schuko European UK Plug USA Plug
Hyperion BarMaster Remote Programmer <i>The BarMaster is a remote programmer used for changing parameters on Hyperion products.</i>	A900-BARMASTER-F	
Hyperion SmartControl Touch <i>SmartControl Touch allows the user to monitor, control and adjust the performance of multiple connected Hyperion ionising bars and sensors via the built-in touchscreen or remotely via PLC, tablet or remote desktop computer.</i>	ASmartCON-TOUCH-LAN	
4-pin M8 2m connection cable <i>For connection of the 906 to a customer's own 24VDC power supply.</i>	A900IPS-PCS2 Contact your local Meech representative for options.	

4. Component overview

The 906 features a status LED to alert the user should any parameter fall outside a predetermined range. A BarMaster or SmartControl Touch is required to both view and modify its output settings.



Hyperion 906 Power Unit overview

4.1. 906 HL variants



**Caution –
Risk of injury & equipment damage.**

The 906 HL must be positioned in a non-hazardous area.
The 906 HL must **NOT** be used/placed in EX rated zones.

The 906 HL variants are intended to drive Meech EX ionising bars, which are designed for use within Hazardous Locations. Each HL variant has the bar it must be used with, as well as its maximum output voltage specified on the label on its enclosure.

HYPERION⁺
906HL 5kV

Meech
MEECH

LED colours

- OK
- Standby
- Low current
- Fault

Input: 24VDC, 0.2-2A max.

Output: 2-5kVAC, 5mA max.

☐ 5.0kV kV

Power supply for 914EX

Area for barcode

WARNING
ISOLATE SUPPLY BEFORE
OPENING COVER

AVERTISSEMENT
ISOLER L'ALIMENTATION AVANT
DE RETIRER LE COUVERCLE

Operating manual
Removal of label
invalidates warranty

Meech International
Tel: +44(0)1993 706700 | sales@meech.com | www.meech.com

CERTIFIED
SWET USCA
E211778
906

D3313 REV1

906 HL 5kV label

HYPERION⁺
906HL 7kV

Meech
MEECH

LED colours

- OK
- Standby
- Low current
- Fault

Input: 24VDC, 0.2-2A max.

Output: 2-7kVAC, 5mA max.

☐ 5.0kV
☐ 7.0kV kV

Power supply for 915EX

Area for barcode

WARNING
ISOLATE SUPPLY BEFORE
OPENING COVER

AVERTISSEMENT
ISOLER L'ALIMENTATION AVANT
DE RETIRER LE COUVERCLE

Operating manual
Removal of label
invalidates warranty

Meech International
Tel: +44(0)1993 706700 | sales@meech.com | www.meech.com

CERTIFIED
SWET USCA
E211778
906


D3314 REV1

906 HL 7kV label

5. Installation

5.1. Mechanical installation

The 906 should be mounted on a surface capable of supporting 4kg, in a well-ventilated area, away from any sources of potential contamination. The 4x 6mm holes in the flange are intended for mounting the 906.




Notice –
Unit failure through contamination will invalidate the warranty.
Ensure the unit is protected from sources of contamination.



Notice –
AC bars not operating in the same phase will not operate at optimal efficiency.
AC bars in close proximity to each other must be connected to the same 906.

5.2. Ionising product connection

The following sections detail how to connect up to 4x Meech AC ionising products via the ports on the 906, as well as detail the necessary electrical inputs.



Caution –

From the HV output sockets and beyond, an ES2 circuit (with respect to IEC62368-1) is present.



Caution –


Injury due to electric shock.

Before making any connections, ensure the 906 is electrically isolated.




Please ensure that only Meech supplied products are connected to HV ports.


1. Remove the lid by unscrewing the retaining screws, then remove the M4 knob.




2. Remove a rubber grommet.




3. Remove the shake proof washer and nut from the ioniser's connector.




4. Insert the ioniser's connector through the hole.




5. Refit the shake proof washer and nut onto the ioniser's connector. Tighten the nut until it is fully secured.




6. Refit the lid and fasten the retaining screws. Tighten the screws until they are fully secured.




7. Remove the transit cap.



8. Connect the 24VDC supply cable into the 24VDC input port.



9. The 906 must be earthed using the M4 earth post. Fit the earth cable, and secure it with the M4 thumbnut.



6. Grounding & 24VDC supply

The 906 must be grounded through the power supply, as well as through the M4 Earth post on the unit.

All power supplies used must be compliant with IEC62368-1 or IEC60950-1.




**Notice –
The 906 must be electrically grounded.**

Failure to do so may damage the equipment and will invalidate the warranty.

6.1. Meech 24VDC switchmode power supply


This refers to the use of a Meech 48W 24VDC switchmode power supply to power the 906, which is grounded internally & supplied with an IEC C13 cable. See section 3.1 for product codes.



6.2. Customers own 24VDC power supply

It is the customers responsibility to check that the 24VDC power supply being connected is grounded.

- The 24VDC power supply must be protected with a 2A fuse.
- Connection to the 906 is through the M8 4-pin socket. The figure below shows the pin numbers of the connector.



Male connector on the 906, as viewed from the mating face.

Pin	Colour	Function	Specification
1	Brown	V_{in} (2A max)	24VDC (22 to 26V)
2	White	Alert output	0V/24VDC
3	Blue	GND	0V
4	Black	Fault output/standby input	0V/24V

7. Operation

The 906 features a status LED that displays the units health and indicates any active alarms. A BarMaster or SmartControl Touch is required for adjustment of its output parameters.

7.1. Using a BarMaster

The BarMaster is connected inline with the 24VDC power supply cable for the 906. Attach the 24VDC power cable to the BarMaster, then fit its cable to the 24VDC input port on the 906. When finished, disconnect the BarMaster and reconnect the 24VDC to the 906.






When powered, the screen will display data similar to below. The arrows keys on the BarMaster keypad can be used to navigate through and adjust the 906 parameters.

```
Meech Ltd
Model 906
FW Ver. 01.00.00
Ser No. 12345678
Output 7.0kV
Load 100%
Alarm True lo
Alarm Drive nfn
Pin 4 Fault Out
```

Pin-4 set to Fault output

```
Meech Ltd
Model 906
FW Ver. 01.00.00
Ser No. 12345678
Output 7.0kV
Load 100%
Alarm True lo
Alarm Drive nfn
Pin 4 Standby In
Standby True lo
```

Pin-4 set to Standby input

BarMaster keypad		
Up		Press to cycle through the parameters
Down		
Left		Press to adjust the parameters
Right		
OK		This button is redundant and has no function.




Please refer to the BarMaster operating manual for more information.

7.2. Using a SmartControl Touch

The SmartControl Touch is powered by a 24VDC and supports direct connection of up to six devices. When used with extension units, up to 30 Meech Hyperion devices can be connected. The output parameters can be adjusted by simply touching the values.

With the 906 connected, its touchscreen will display a screen similar to below.



The image shows the SmartControl Touch user interface for the 906 device. The interface is displayed on a touchscreen and features a blue header bar with the 'SmartControl™' logo. Below the header, there is a navigation bar with various port labels. The main display area is divided into sections. On the left, the 'HYPERION™ A Meech Innovation' logo is visible. To the right, connection details are shown: 'Connection port: ExtB, port 1', 'Location Name: Location', 'Model and Version: 906, FW Ver. 01.00.00', and 'Serial No: 01514550'. Below this, a table lists adjustable parameters: Output (5 kV), Load (8 %), Alarm Level (0 %), Standby Off (toggle switch), and Status Ok/Run (0 RTFM). At the bottom, the user is identified as 'User: super' and the 'Comms Alarm' is shown as a toggle switch. The interface is powered by 'REXYGEN'.

Parameter	Value
Output	5 kV
Load	8 %
Alarm Level	0 %
Standby Off	<input type="checkbox"/>
Status Ok/Run	0 RTFM

SmartControl Touch user interface for 906



Notice –
Ensure the 906 is correctly configured before connecting the SmartControl Touch.

Pin-4 of the 24VDC input port is to fault output by default. Before connecting a SmartControl Touch, ensure that Pin-4 is set to fault output.



Please refer to the SmartControl Touch operating manual for more information.

7.3. Modifying the output parameters



Notice –

Ionising equipment will not operate at their optimum and may be damaged if the output parameters are incorrectly set.

Ensure the output parameters are correct for the connected ionising equipment.



Please refer to the operating manual of the connected ionising product for specific operating parameters.

7.3.1. Health monitoring

The performance of the 906 can be measured by monitoring its load percentage with a BarMaster/ SmartControl Touch. Connecting multiple ionisers to the 906 will increase its load, up to 100%.

When the load reaches either 0% or 100%, the status LED on the 906 will either flash red or be solid red, and an alarm signal will be sent from either Pin-2 (white) or Pin-4 (black) of the 24VDC input port. When the load reaches 100%, the unit will cut out to ensure operator safety and to protect any attached ionisers.

Over an ionisers life time, its emitter pins will gradually wear down and dirt will accumulate on both the pins and its body. This will reduce the ionisers performance, and will slightly decrease the 906 load percentage. As part of regular maintenance, it is recommended to clean both the emitter pins and body of the ioniser. Regular cleaning will restore the load percentage, extend the ionisers lifespan and ensure optimal performance.

7.3.2. Voltage

The voltage must be set dependent on the connected ioniser, as well as the distance between the ioniser and the target material. For example, a close range or delicate application relies on a lower output voltage, whereas a longer range or heavily charged target will require a higher output voltage.

Generally, Meech ionising products should be run at their default voltage setting for optimum performance. The voltage output of the 906 depends on the variant, but it can be adjusted by using a BarMaster/SmartControl Touch.

The table below lists the operating voltages for ionising products compatible with the 906.

Ionising product	Operating voltage
914 AC Ionising Bar	5kVAC
914EX Hazardous Area AC Ionising Bar	5kVAC
915 AC Ionising Bar	7kVAC
915EX Hazardous Area AC Ionising Bar	7kVAC
925 High Temperature AC Ionising Bar	6kVAC
954v3 Ionising Nozzle/Air Gun	5kVAC


7.4. Remote control

The 906 is capable of being controlled remotely, through 24VDC input port or SmartControl. This allows the 906 to be toggled in and out of standby mode when connected to a separate PLC/switch system.

7.4.1. 24VDC input port

By adjusting the Pin-4 (black) setting from Fault output to Standby input with a BarMaster, standby mode is toggled by either connecting Pin-4 to 24V (Standby True = Hi) or 0V GND (Standby True = Lo).

Refer to section 6.2 'Customers own 24VDC power supply' for more information on the 24VDC port.



7.4.2. Software

Once the 906 is connected to a SmartControl Touch through the 24VDC input port, standby mode can be toggled through its interface as seen below (circled).

The image displays two screenshots of the SmartControl™ interface, showing the process of toggling standby mode.

Top Screenshot: Standby mode off

- Header:** SmartControl™
- Navigation:** < EXT8 PORT 10 EXT8 PORT 11 EXT8 PORT 12 EXT8 PORT 1 TRND EXT8 PORT 2 TRND EXT8 PORT 3 TRND EXT8 PORT 4 TRND EXT8 PORT 5 TRND EXT8 PORT 6 TRND EXT8 PORT 7 TRND >
- Logos:** HYPERION™ A Meech Innovation, Meech
- Connection Info:** Connection port: ExtB, port 1; Location Name: Location; Model and Version: 906, FW Ver. 01.00.00; Serial No: 01514550
- Controls:** Output: 5 kV; Load: 8 %; Alarm level: 0 %; **Standby Off** (circled); Status: 0 RTFM
- Footer:** User: super; Comms Alarm: (off); Powered by REXYGEN

Bottom Screenshot: Standby mode on

- Header:** SmartControl™
- Navigation:** < EXT8 PORT 10 EXT8 PORT 11 EXT8 PORT 12 EXT8 PORT 1 TRND EXT8 PORT 2 TRND EXT8 PORT 3 TRND EXT8 PORT 4 TRND EXT8 PORT 5 TRND EXT8 PORT 6 TRND EXT8 PORT 7 TRND >
- Logos:** HYPERION™ A Meech Innovation, Meech
- Connection Info:** Connection port: ExtB, port 1; Location Name: Location; Model and Version: 906, FW Ver. 01.00.00; Serial No: 01514550
- Controls:** Output: 5 kV; Load: 0 %; Alarm level: 0 %; **Standby On** (circled); Status: 10 RTFM
- Footer:** User: super; Comms Alarm: (off); Powered by REXYGEN



Please refer to the SmartControl Touch operating manual for more information.



















8. Monitoring

The Hyperion 906 Power Unit continually monitors its internal health and can trigger an alarm should any parameter fall outside a predetermined range.

Alarms can be monitored either via the status LED, or through the alarm outputs.

8.1. Status LED

The LED colour combinations are below:






LED colours	Alarm status	Description - <i>corrective actions</i>
Green 	 Normal	Normal operation
Yellow 	 Normal	Standby - HV output is off
Flashing green 	 Normal	Normal operation - BarMaster/SmartControl connected
Flashing yellow 	 Normal	Standby - HV output is off, BarMaster/SmartControl connected
Red 	 Fault	HV overcurrent - <i>Check outputs/reduce load</i>
Flashing red 	 Alert	Low ion current - <i>Check attached ionisers for contamination</i>
Flashing green/red 	 Fault	Internal issue - <i>Restart the device</i>
Flashing red/yellow 	 Fault	Real Time Fault Monitoring (RTFM) - <i>Refer to section 8.1.1.</i>
Flashing green/yellow 	 Alert	Real Time Fault Monitoring (RTFM) - <i>Refer to section 8.1.1.</i>

- **Fault** – The 906 has a fault, and the output has been shut off.
- **Alert** – Attention may be required for the 906.

If the 906 has a fault, perform the *corrective actions* above then cycle power to reset the unit.

8.1.1. Real Time Fault Monitoring codes

The following RTFM codes may be observed on the status LED to provide a more detailed alarm overview. The LED will flash green or red with up to 5 yellow flashes, to display different fault codes.

LED colours	Alarm status	Description – <i>Corrective actions</i>
Green & 2 yellow flashes 	Alert	HV output: Approaching current limit – <i>Reduce output load</i>
Green & 3 yellow flashes 		24VDC power supply: Approaching under voltage – <i>Check power supply</i>
Green & 5 yellow flashes 		Internal temperature: Approaching temperature limit – <i>Ensure 906 has sufficient cooling</i>
Red & 4 yellow flashes 	Fault	24VDC power supply: Reached over voltage – <i>Check power supply</i>
Red & 5 yellow flashes 		Internal temperature: Reached temperature limit – <i>Ensure 906 has sufficient cooling</i>

8.2. Remote monitoring

8.2.1. Alarm outputs

Remote alarm monitoring is provided by Pin-2&4 of the 24VDC input port. These alarm signals output either 0 or 24V and are suitable for direct connection to a PLC input, or to control an external 24V relay.

- **Alert (Pin-2 white)**
This pin is used to report when attention may be required for the 906.
- **Fault (Pin-4 black)**
This pin is used to report when the 906 has a fault, and the output has been shut off (unless configured as standby input – see section 7.4.).

On 906 power-up, Pin 2&4 will remain in Hi state for up to 60 seconds before they are used as outputs.

Note: When a BarMaster remote programmer is connected, alert and fault outputs are temporarily disabled.


8.2.2. Alarm output drive options

Using a BarMaster*, the alarm output can be configured to meet most requirements. As standard, the 906 will be supplied with a factory preset configuration of Output drive = NPN, where Alarm True = Lo.

There are 3 different output drive options which are designed to allow easy integration with most PLC equipment.

1. **Output drive = NPN** – 24V is supplied via an internal 2.2kΩ resistor, 0V is supplied directly. **
2. **Output drive = PNP** – 24V is supplied directly, 0V is supplied via an internal 2.2kΩ resistor. **
3. **Output drive = N+P** – Both 24V & 0V are supplied directly. ***

The output polarity (Alarm True) can be set to go to Hi (24V) or Lo (0V) when there is an issue.




* = Please refer to BarMaster operating manual

** = Using NPN (default Hi) or PNP (default Lo) allows for multiple products to be connected in parallel, triggering a common alert without interfering with each other's operation.


*** = Using N+P **does not** allow for any products to be connected in parallel.

Output Drive = NPN
Alarm True = Lo




Default: Can be used with multiple devices in parallel.

Output Drive = PNP
Alarm True = Lo




Output Drive = N+P
Alarm True = Lo




When Alarm True = Lo, OK = 24V & Alert/Fault = 0V


Output Drive = NPN
Alarm True = Hi



Output Drive = PNP
Alarm True = Hi



Output Drive = N+P
Alarm True = Hi



On power on, the output signal stays high for 60 seconds, so Alarm True=Hi may cause issues on power cycle.

When Alarm True = Hi, OK = 0V & Alert/Fault = 24V

9. Technical & construction data

Dimensions (LxWxH)	120mm x 130mm x 126mm	
Weight	Approx 3.85kg	
Maximum ambient temperature	55°C	
Mounting	4x 6mm holes	
Mounting height	To comply with UL 62368-1, the 906 must be mounted at a height ≤2m	
Enclosure	Powder coated steel	
Electrical connections	4-pin M8, earth terminal & M4 HV output post	
Input current	Maximum 2A	
Input voltage	24VDC (22 to 26VDC)	
Output ports	4x HV connection ports	
Output current	Maximum 5mA	
Output voltage	A906-5kV	2 to 7kVAC (Preset to 5kV) [†]
	A906-7kV	2 to 7kVAC (Preset to 7kV) [†]
	A906HL-5kV	2 to 5kVAC (Default 5kV) [†]
	A906HL-7kV	2 to 7kVAC (Default 7kV) [†]
Output frequency	70Hz	
Alarm output/standby input	Dual outputs for Alert/Fault monitoring (0/24V)*: 1x Alert output 1x Fault output/standby input	
Alarm output drives	Compatible with IEC 61131-2 type 1,2,3 plc inputs	
Local indication	Green/yellow/red LED	
Protection class	IP40 construction	



* = Adjustable via BarMaster



† = Adjustable via BarMaster or SmartControl Touch

10. Technical drawings



Contact Meech customer services at customerservice@meech.com for additional technical drawings, providing the model code (see section 3).

Page	PulseDrive variant	Variant model code
26-27	Hyperion 906 Power Unit	A906-5kV
		A906-7kV





MOUNTING HOLE POSITIONS



11. Maintenance

The 906 should be regularly cleaned with a dry cloth to keep it free from dust and other contaminants.

Should the 906 become wet, ensure it is thoroughly dried before restoring power to it.

12. CE approval

A CE Declaration of Conformity for this product exists and can be provided on request.



13. UL approval

The Hyperion 906 Power Unit is compliant with UL Listing requirements.

A copy of the UL certification can be found at www.meech.com/download/ul-certificates/



14. Health & safety

- **Emission of Ozone**
Considerably lower than the international standard of 0.1ppm.
- **Output current**
The maximum output current is less than 5mA to prevent serious harm to the operator, nevertheless any contact with the output post should be avoided where possible.
- **Usage restrictions**
This equipment is not suitable for use in locations where children are likely to be present.

15. Repairs & warranty

The Hyperion 906 Power Unit is warrantied by Meech International Ltd. to the original purchaser against defects in material and workmanship for 2 years after shipment.

For support, contact your local Meech representative. Alternatively, more details can be found at:

<https://meech.com>

support@meech.com

+44 (0)1993 706700

Meech International

2 Network Point
Range Road
Witney, Oxfordshire
OX29 0YN
United Kingdom
Tel: +44 (0)1993 706700
Email: sales@meech.com

Meech Static Eliminators USA

1298 Centerview Circle
Akron, Ohio 44321
United States
Tel: +1 330 564 2000
Fax: +1 330 564 2005
Email: info@meech.com

Meech Static Eliminators (Shanghai)

7G, 7F, LP Tower
#25 Xianfeng Road
201103 Shanghai
China
Tel: +86 400 820 0102
Fax: +86 21 6405 7736
Email: china@meech.com

Meech Shavotech

29/2, Kharadi
Off Pune-Nagar Road
Old Kharadi Mundhwa Road
Pune: 411014, Maharastra
India
Tel: +91 (0)703 093 8211 / +91 (0)741 000 4817
Fax: +91 (080) 28395963
Email: india@meech.com

Meech Elektrostatik SA

Kaiserbaracke 166
B-4780 St. Vith
Belgium
Tel: +32 (0)80 670 204
Fax: +32 (0)80 862 821
Email: mesa@meech.com

Meech International (Singapore)

7 Temasek Boulevard
12 - 07 Suntec Tower One
Singapore
038987
Tel: +65 65918859
Email: singapore@meech.com

Meech CE

Gábor László utca 2
Budapest 1041
Hungary
Tel: +36 1 7977039 / +36 30 2803334
Email: ce@meech.com



View and save a digital version of this operating manual by
following the QR code or visiting www.meech.com/downloads:

